



# 130

## RECEIVER HITCH

### 1999 & Up Honda Odyssey

#### INSTALLATION INSTRUCTIONS

1. **Check** all parts. **Read and understand** instructions completely before beginning installation.

6) 12mm x 40 x 1.25 **Hex Bolts**  
6) 12mm **Lockwashers**

6) 14mm x 40 **Hex Bolts**  
6) 14mm **Hex Nuts**

6) 14mm **Lockwashers**  
6) **HD Flatwashers**

2. **Clean** the frame of mud and undercoating. Then the 12mm -1.25 weldnuts need to be cleaned of all paint and dirt. That is a very fine thread nut. You may want to run a 12mm - 1.25 tap into the nuts, making sure the holes are clean. You should at least run the bolts into each hole making sure they thread freely.

3. **Install** the hangers on each side using (3) 12mm hex bolts, flat washers , and lockwashers on each side. Loosely tighten all the hex bolts.

4. **Slip** the center section into place between the two hangers and secure with (6) 14mm hex bolts, (3) on each side. Use the 14mm hex nuts and 14mm lockwashers on each bolt and snug.

5. **Snug** all bolts on the hangers first, then the center section.

6. **Torque** the 12mm Bolts to 65 ft/lbs. 14mm bolts to 100 ft/lbs. Use a torque wrench

<b>GROSS LOAD</b>		
HITCH TYPE	MAX TRL WT (LB)	MAX TONGUE WT (LB)
WEIGHT DISTRIBUTION	5,000	500
WEIGHT CARRYING	3,500	350

Periodically check this receiver hitch to ensure that all bolts are tight and all components sound.

The manufacturer warrants this product to be free of defects in material or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, the manufacturer may repair or replace the product, at its option, when product is returned, prepaid, with proof of purchase to the manufacturer. Alteration to, misuse of, or improper installation of product voids this warranty. Manufacturer's liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.

Quality S Manufacturing, Inc., Phoenix, AZ

