



267

RECEIVER HITCH

GMC Acadia, Saturn Outlook, Buick Enclave, Chevrolet Traverse 2007 & Up

INSTALLATION INSTRUCTIONS

1. **Check** all parts. **Read and understand** instructions completely before beginning installation.
 - 2) Hitch Hangers
 - 1) Hitch Center Section
 - 6) 12mm - 1.75 x 40mm Hex Bolts
 - 6) 12mm Lock Washers
 - 6) 1/2 " HD Flat Washers
 - 6) 14mm - 2.0 x 40mm Hex Bolts
 - 6) 14mm Hex Nuts
 - 6) 14mm Lockwashers
2. **Remove** the bumper fascia door and return to the owner. Rotate the spare tire plastic cover to the passenger side about 12". This will help clear hitch.
3. **If you lower** the exhaust it will help ease installation. (You can use a spray lubricant , or soap and water on the rubber isolator and rod to help removal) Clean the frame rails and bumper beam of all debris.
4. **Raise** the hitch hangers into position and align slots with the 12mm- 1.75 weld nuts in the bottom of the frame rails. Loosely secure the hangers in place with four 12mm - 1.75 x 40mm hex bolts, four 12mm lockwashers and four 1/2 " HF flat washers.
5. **Raise** the center section between the two hangers. Secure to the hangers with six 14mm - 2.0 x 40mm hex bolts, 14mm lockwashers, and 14mm hex nuts.
6. **Secure** the receiver tube bracket to the bumper beam with two 12mm - 1.75 x 40mm hex bolts, 12mm lock washers, and 1/2 " HD flat washers.
7. **Center** the hitch and snug all bolts.
8. **Torque** all bolts starting with the hangers. Torque all 12mm - 1.75 bolts to 65 ft/lbs, 14mm - 2.0 bolts to 100 ft/lbs.
9. **Raise** the exhaust into position and reinstall the rubber isolators.

GROSS LOAD		
HITCH TYPE	MAX TRL WT (LB)	MAX TONGUE WT (LB)
WEIGHT DISTRIBUTION	6,000	600
WEIGHT CARRYING	5,000	500

Do not exceed vehicle manufacturer's recommended towing capacity

Periodically check this receiver hitch to ensure that all bolts are tight and all components sound.

The manufacturer warrants this product to be free of defects in material or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, the manufacturer may repair or replace the product, at its option, when product is returned, prepaid, with proof of purchase to the manufacturer. Alteration to, misuse of, or improper installation of product voids this warranty. Manufacturers liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.

Quality S Manufacturing, Inc., Phoenix, AZ

